

## WIDE FORMAT LAMINATING SYSTEMS

Easymount® is designed to perform and built to last.



▲ EM-1600SH

### KEY FEATURES

- 6m/20ft a minute
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel
- 25mm/1" mounting thickness

### GREAT FOR USE IN

- Sign makers
- Print finishers

### IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage and many more...

### Design & Performance

The Easymount® laminators are designed to perform and built to last.

Their advanced features allow you to laminate and mount.

Designed in-house by Vivid, the Easymount® range gives your business extra capacity by allowing you to offer your customers a complete service that you previously had to outsource.

### Features

- Solid heavy duty construction
- Release liner take-up
- Adjustable rollers up to 20mm/0.8"
- Large rollers for even pressure
- Handy reverse mechanism
- Foot pedal for controlled operation

Specifications	EM-1400SH	EM-1600SH	EM-1400C	EM-1600C
Laminating Speed (m/ft/min)	6m/20ft	6m/20ft	6m/20ft	6m/20ft
Max. Width (mm/inches)	1400mm/55"	1600mm/63"	1400mm/55"	1600mm/63"
Mounting Thickness (mm/inches)	25mm/ 1"	25mm/ 1"	25mm/ 1"	25mm/ 1"
Roller Diameter (mm/inches)	112mm/4"	130mm/5"	112mm/4"	130mm/5"
Laminating Temperature (°C/°F)	0-60°C/32-140°F	0-60°C/32-140°F	-	-
Control Panel	Digital	Digital	Digital	Digital
Pressure Adjustment	Manual/Gauge	Manual/Gauge	Manual/Gauge	Manual/Gauge
Film Core (mm/inches)	77mm/3"	77mm/3"	77mm/3"	77mm/3"
Power Supply AC (V-Hz)	220/240-50-60	220/240-50-60	220/240-50-60	220/240-50-60
Power Consumption (W)	1300	1500	50	50
Overall Dimensions (mm/inches)	1990x650x1255mm/ 78x26x49"	2190x650x1255mm/ 86x26x49"	1990x650x1255mm/ 78x26x49"	2190x650x1255mm/ 86x26x49"
Gross Machine Weight (Kg/lbs)	210Kg/462lbs	245Kg/540lbs	210Kg/462lbs	245Kg/540lbs
Warranty	1 year	1 year	1 year	1 year

Additional sizes: EM-1200 & EM-2100. In both single hot and cold options