

Self-adhesive Specialities

Toner
Water
(eco) Solvent
UV Curable
Latex

LFM360 Self-adhesive PET film

155 µm

Product Description White matt self-adhesive polyester film with silicon paper release liner for indoor use.

Physical Properties	Total thickness (µm)	150		Adhesion (N/25mm)	3.5-5.0	(A.F.E.R.A.)
	Total weight (g/m ²)	190		Adhesion after 24h (N/25mm)	10	(A.F.E.R.A.)
	Thickness film (µm)	50		Temperature range (°C)	5 - 80	
	Weight paper liner (g/m ²)	100				

Applications/features POS, Signs
Labels, stickers
Good adhesion on flat lacquered surfaces boards, plastics, glass, metal
Excellent image quality
Suited for Océ CrystalPoint® Technology

Available Widths (mm)	3"core	610	914								
	Refer for our current offering to mediaguide.oce.com										

Storage Conditions Temperature 10-20°C, Relative Humidity 50%
Repack opened rolls when not in use.

Print Conditions Best results are obtained between 10-30°C and 40-70% RH.

Environment, Health & Safety No Material Safety Data Sheet required.

Lamination Compatibility	Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
	yes	no	no	

Outdoor Use This film is not suited for outdoor use.

Colour Profiles Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on mediaguide.oce.com

Processing
Guidelines

Printing guidelines

LFM360 is compatible with ColorWave printers with Océ CrystalPoint® technology. High quality print-modes are recommended for best results.

It is recommended to handle the media with cotton gloves. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects. Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printers.

Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon colour profiles include recommended ink restrictions and printer settings for Canon supported printers.

Application guidelines

Use a 100% felt squeegee to avoid scratching the print surface

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.